LIGHT LABORATORY INC.
8165 E Kaiser Blvd.
Anaheim, CA 92808
www.lightlaboratory.com

NVLAP TESTING
NVLAP LAB CODE 200927-0

Report No: L032110102 **Issue Date: 3/5/2021**

Report Prepared For: Hunter Industries
1940 Diamond Street,San Marcos, CA 92078

Model Number: LDLED35WWG

Test: Photometric/Colorimetric/Electrical Test

Standards Used: Appropriate part or all test guidelines were used for test performed:

IESNA LM79: 2008 Approved Methods for Electrical and Photometric Measurements of Solid-State Lighting Products

ANSI NEMA ANSLG C78.377: 2008 Specification of the Chromaticity of Solid State Lighting Products

ANSI C82.77:2002: Harmonic Emission Limits-Related Quality Requirements for Lighting Equipment

Description of Sample: Client submitted the sample. Received in working and undamaged condition. No modifications were necessary.

Special Test Condition: Fixture is tested with no special conditions.

Sample Arrival Date: 3/2/21

Date of Tests: 3/3/21 - 3/5/21

Seasoning of Sample: No seasoning was performed in accordance with IESNA LM-79.

Equipment List

Equipment Used	Model No	Stock No	Calibration Due Date
Chroma Programmable AC Source	61604	PS-AC02	--
Yokogawa Digital Power Meter	WT210	MT-EL06-S4	1/9/22
BK PRECISION	1747	PS-DC04	1/10/22
Fluke Digital Thermometer	52K/J	MT-TP05	1/10/22
LLI Type C Goniophotometer System	RMG-C-MKII	CD-LL04-GC	--
LLI 2M Sphere	2MR97	CD-SN03-S2	--
LLI Spectroradiometer	SPR-3000	MT-SC01-S2	Before Use

LIGHT LABORATORY INC.
8165 E Kaiser Blvd.
Anaheim, CA 92808
www.lightlaboratory.com

NVLAP TESTING
NVLAP LAB CODE 200927-0

General Information	
Manufacturer:	Hunter Industries
Model Number:	LDLED35WWG
Driver Model Number:	N/A

Test Summary	
Total Lumens:	93.80
Efficacy:	63.08
Color Redering Index:	84.9
Correlated Color Temperature:	2591
Input Voltage (VAC/60Hz):	12.00
Input Current (Amp):	0.1310
Input Power (W):	1.49
Input Power Factor:	0.9444
Current ATHD (%):	32.2%

Test Condition	
Ambient Temperature (°C):	25.0
Stabilization Time (Hours):	0:45
Total Operating Time (Hours):	1:15





FIG. 1 LUMINAIRE

LIGHT LABORATORY INC.
8165 E Kaiser Blvd.
Anaheim, CA 92808
www.lightlaboratory.com

Report No: L032110102

NVLAP TESTING
NVLAP LAB CODE 200927-0

Colorimetry Test Results




CRI & CCT

x	0.4696
y	0.4135
u'	0.2675
v'	0.5299
CRI	84.90
CCT	2591
Duv	0.00035

R Values

R1	86.17
R2	97.57
R3	89.91
R4	82.20
R5	87.41
R6	95.99
R7	79.48
R8	60.35
R9	21.08
R10	94.83
R11	83.12
R12	82.71
R13	89.40
R14	95.24
R15	77.43



LIGHT LABORATORY INC.
8165 E Kaiser Blvd.
Anaheim, CA 92808
www.lightlaboratory.com

NVLAP TESTING
NVLAP LAB CODE 200927-0

Test Methods

Photometric Measurements - Goniophotometer

A Custom Light Laboratory Type C Rotating Mirror Goniophotometer was used to measure candelas(intensity) at each angle of distribution as defined by IESNA for the appropriate fixture type.

Ambient temperature is set to 25^{o}C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25^{o}C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

Spectral Measurements - Integrating Sphere

A Sensing Spectroradiometer SPR-3000, in conjunction with Light Laboratory 2 meter integrating sphere was used to measure chromaticity coordinates, correlated color temperature(CCT) and the color rendering index(CRI) for each sample.

Ambient temperature is set to 25^{o}C and is measured from the center of the fixture, within 1ft from the outside of the fixture. Temperature is maintained at 25^{o}C throughout the testing process and the sample is stabilized for at least 30mins and longer as necessary for the sample to achieve stabilization.

Electrical measurements are measured using the listed equipment.

Disclaimers:

This report must not be used by the customer to claim product certification, approval or endorsement by NVLAP, NIST or any agency of Federal Government.

Report Prepared by : Keyur Patel

Test Report Reviewed by:

Steve Kang
Quality Assurance

**Attached are photometric data reports. Total number of pages: 14*

LIGHT LABORATORY INC.
8165 E. Kaiser Blvd. Anaheim, CA 92808
www.lightlaboratory.com

Photometric Test Report

IES ROAD REPORT
PHOTOMETRIC FILENAME : L032110102.IES

DESCRIPTIVE INFORMATION (From Photometric File)

IESNA:LM-63-2002
[TEST] L032110102
[TESTLAB] LIGHT LABORATORY, INC. (www.lightlaboratory.com)
[ISSUEDATE] 3/5/2021
[MANUFAC] Hunter Industries
[LUMCAT] LDLED35WWG
[LUMINAIRE] LD, G4 LED35W, 2700K, WG
[BALLASTCAT] N/A
[OTHER] INDICATING THE CANDELA VALUES ARE ABSOLUTE AND
[MORE] SHOULD NOT BE FACTORED FOR DIFFERENT LAMP RATINGS.
[INPUT] 12.0VAC, 1.49W
[TEST PROCEDURE] IESNA:LM-79-08

CHARACTERISTICS

IES Classification	Type II
Longitudinal Classification	Very Short
Lumens Per Lamp	N.A. (absolute)
Total Lamp Lumens	N.A. (absolute)
Luminaire Lumens	94
Downward Total Efficiency	N.A. (absolute)
Total Luminaire Efficiency	N.A. (absolute)
Luminaire Efficacy Rating (LER)	63
Total Luminaire Watts	1.49
Ballast Factor	1.00
Upward Waste Light Ratio	0.00
Maximum Candela	38.77
Maximum Candela Angle	290H 10V
Maximum Candela (<90 Degrees Vertical)	38.77
Maximum Candela Angle (<90 Degrees Vertical)	290H 10V
Maximum Candela At 90 Degrees Vertical	0 (0.0% Luminaire Lumens)
Maximum Candela from 80 to <90 Degrees Vertical	5.69 (6.1% Luminaire Lumens)
Cutoff Classification (deprecated)	N.A. (absolute)

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES ROAD REPORT
PHOTOMETRIC FILENAME : L032110102.IES

LUMINAIRE CLASSIFICATION SYSTEM (LCS)

	Lumens	% Lamp	% Luminaire
FL - Front-Low (0-30)	15.3	N.A.	16.3
FM - Front-Medium (30-60)	25.9	N.A.	27.6
FH - Front-High (60-80)	6.5	N.A.	6.9
FVH - Front-Very High (80-90)	0.6	N.A.	0.6
BL - Back-Low (0-30)	14.7	N.A.	15.7
BM - Back-Medium (30-60)	24.2	N.A.	25.8
BH - Back-High (60-80)	6.1	N.A.	6.5
BVH - Back-Very High (80-90)	0.5	N.A.	0.5
UL - Uplight-Low (90-100)	0.0	N.A.	0.0
UH - Uplight-High (100-180)	0.0	N.A.	0.0
Total	93.8	N.A.	100.0
BUG Rating	B0-U0-G0		

ZONAL LUMEN SUMMARY

Zone	%
0-20	15
0-30	32
0-40	51.8
0-60	85.3
0-80	98.8
0-90	100
10-90	96.1
20-40	36.8
20-50	55.8
40-70	42.6
60-80	13.5
70-80	4.4
80-90	1.2
90-110	0
90-120	0
90-130	0
90-150	0
90-180	0
110-180	0
0-180	100

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES ROAD REPORT
PHOTOMETRIC FILENAME : L032110102.IES

CANDELA TABULATION

Vert. Angles	Horizontal Angles									
	0	**5**	**10**	**15**	**20**	**25**	**30**	**35**	**40**	**45**
0	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18
5	38.53	38.49	38.35	38.39	38.25	38.28	38.25	38.14	38.11	38.14
10	38.32	38.11	38.00	37.97	37.97	37.97	37.93	37.79	37.76	37.65
15	37.69	37.62	37.62	37.62	37.51	37.37	37.34	37.16	36.95	36.85
20	36.99	36.81	36.64	36.57	36.40	36.12	36.05	36.08	35.84	35.63
25	35.52	35.28	35.14	35.00	35.00	34.79	34.79	34.47	34.44	34.30
30	32.87	32.73	32.62	32.62	32.66	32.55	32.62	32.59	32.48	32.48
35	29.13	28.96	28.82	28.89	28.89	29.06	29.31	29.65	29.69	29.76
40	24.80	24.66	24.62	24.73	24.83	25.18	25.53	25.92	26.23	26.76
45	20.26	20.19	20.26	20.47	20.57	20.78	21.17	21.59	22.04	22.63
50	16.00	15.96	16.00	16.07	16.28	16.63	16.98	17.43	17.92	18.58
55	11.95	11.91	11.95	12.09	12.26	12.50	12.89	13.24	13.76	14.32
60	8.91	8.87	8.91	8.98	9.15	9.29	9.54	9.85	10.16	10.62
65	6.50	6.46	6.50	6.53	6.60	6.71	6.85	7.06	7.27	7.58
70	4.54	4.51	4.54	4.54	4.61	4.65	4.72	4.82	4.96	5.13
75	3.00	3.00	3.00	3.00	3.04	3.07	3.14	3.18	3.25	3.32
80	1.75	1.75	1.75	1.75	1.78	1.78	1.82	1.85	1.89	1.92
85	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.87	0.91	0.91
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Angles	Horizontal Angles									
	50	**55**	**60**	**65**	**70**	**75**	**80**	**85**	**90**	**95**
0	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18
5	38.04	38.00	37.93	37.93	37.93	37.86	37.83	37.83	37.72	37.76
10	37.55	37.41	37.27	37.13	37.06	37.06	37.09	37.09	37.09	37.06
15	36.81	36.71	36.43	36.26	36.05	35.98	35.91	35.91	35.84	35.63
20	35.45	35.35	35.28	35.00	34.86	34.58	34.54	34.40	34.30	34.26
25	34.06	33.85	33.60	33.39	33.25	33.08	32.87	32.69	32.66	32.48
30	32.31	32.06	31.89	31.65	31.40	31.05	30.95	30.77	30.88	30.74
35	29.86	29.86	29.65	29.38	29.24	28.99	28.71	28.50	28.43	28.33
40	26.96	27.07	27.00	26.93	26.69	26.48	26.30	26.16	25.95	25.81
45	23.19	23.58	23.75	23.82	23.68	23.68	23.47	23.26	23.05	22.77
50	19.04	19.60	19.98	20.29	20.33	20.33	20.19	19.91	19.73	19.56
55	14.78	15.26	15.86	16.24	16.49	16.52	16.45	16.28	16.00	15.89
60	11.14	11.56	11.98	12.40	12.68	12.78	12.78	12.64	12.40	12.30
65	7.89	8.28	8.59	8.87	9.15	9.33	9.36	9.22	9.05	8.98
70	5.34	5.52	5.80	6.01	6.18	6.32	6.39	6.36	6.25	6.22
75	3.46	3.56	3.67	3.84	3.95	4.05	4.12	4.19	4.26	4.23
80	1.96	2.03	2.10	2.17	2.27	2.34	2.45	2.52	2.66	2.55
85	0.94	0.94	0.98	1.01	1.05	1.08	1.12	1.12	1.15	1.15
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Angles	Horizontal Angles									
	100	**105**	**110**	**115**	**120**	**125**	**130**	**135**	**140**	**145**
0	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18
5	37.69	37.76	37.69	37.69	37.58	37.58	37.58	37.51	37.55	37.65
10	36.95	36.88	36.71	36.71	36.61	36.71	36.68	36.64	36.68	36.78
15	35.56	35.63	35.63	35.66	35.66	35.66	35.49	35.45	35.63	35.77
20	34.23	34.23	34.20	34.23	34.16	34.06	34.09	34.13	34.26	34.30
25	32.41	32.45	32.41	32.31	32.31	32.31	32.24	32.38	32.45	32.45
30	30.53	30.49	30.53	30.49	30.56	30.42	30.32	30.28	30.25	30.21

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.

Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES ROAD REPORT
PHOTOMETRIC FILENAME : L032110102.IES

CANDELA TABULATION - (Cont.)

35	28.22	28.08	28.05	28.08	28.05	28.01	27.91	27.84	27.63	27.38
40	25.81	25.64	25.57	25.64	25.57	25.50	25.18	24.87	24.55	24.14
45	22.84	22.77	22.77	22.67	22.56	22.32	21.94	21.45	20.92	20.47
50	19.56	19.53	19.53	19.35	19.14	18.79	18.23	17.74	17.12	16.63
55	15.93	15.86	15.72	15.54	15.16	14.78	14.29	13.69	13.24	12.75
60	12.33	12.26	12.09	11.84	11.56	11.14	10.72	10.27	9.89	9.57
65	9.05	8.91	8.73	8.49	8.24	8.00	7.65	7.37	7.09	6.88
70	6.22	6.04	5.87	5.73	5.52	5.38	5.13	4.93	4.79	4.61
75	4.16	4.02	3.81	3.67	3.53	3.39	3.25	3.14	3.04	2.93
80	2.55	2.45	2.31	2.10	1.96	1.89	1.78	1.71	1.68	1.61
85	1.08	1.01	0.98	0.91	0.87	0.80	0.77	0.73	0.70	0.66
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Angles	**Horizontal Angles**									
	150	**155**	**160**	**165**	**170**	**175**	**180**	**185**	**190**	**195**
0	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18
5	37.72	37.79	37.79	37.93	37.93	37.97	38.00	38.00	38.07	38.07
10	36.92	36.99	37.06	37.20	37.27	37.27	37.30	37.34	37.37	37.48
15	35.77	35.77	35.91	36.01	36.08	36.15	36.33	36.43	36.54	36.71
20	34.30	34.33	34.40	34.47	34.47	34.51	34.68	34.82	34.96	35.14
25	32.41	32.38	32.41	32.45	32.55	32.69	32.73	32.76	32.94	33.11
30	30.07	29.93	29.93	29.83	29.79	29.83	29.90	30.04	30.21	30.49
35	27.14	26.86	26.62	26.55	26.44	26.34	26.37	26.58	26.72	26.90
40	23.75	23.44	23.05	22.77	22.63	22.56	22.60	22.70	22.88	23.12
45	19.98	19.56	19.21	18.90	18.76	18.65	18.65	18.72	18.86	19.04
50	16.21	15.72	15.44	15.19	15.02	14.91	14.88	14.91	15.09	15.26
55	12.40	12.09	11.81	11.63	11.49	11.46	11.42	11.46	11.49	11.67
60	9.26	9.05	8.91	8.73	8.66	8.59	8.56	8.59	8.66	8.73
65	6.71	6.50	6.39	6.32	6.25	6.18	6.18	6.18	6.22	6.29
70	4.51	4.40	4.33	4.26	4.23	4.19	4.16	4.19	4.19	4.26
75	2.86	2.79	2.72	2.69	2.62	2.62	2.59	2.62	2.62	2.69
80	1.54	1.50	1.47	1.43	1.40	1.40	1.40	1.40	1.40	1.43
85	0.63	0.63	0.59	0.56	0.56	0.56	0.56	0.56	0.59	0.59
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Angles	**Horizontal Angles**									
	200	**205**	**210**	**215**	**220**	**225**	**230**	**235**	**240**	**245**
0	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18
5	38.11	38.14	38.21	38.25	38.21	38.18	38.07	38.18	38.07	38.18
10	37.51	37.62	37.76	37.79	37.79	37.79	37.86	37.93	37.93	37.97
15	36.81	36.85	36.92	37.06	37.23	37.34	37.37	37.51	37.65	37.76
20	35.31	35.45	35.59	35.80	35.98	36.19	36.29	36.64	36.74	37.02
25	33.36	33.71	33.95	34.20	34.47	34.68	35.14	35.31	35.56	35.91
30	30.81	31.09	31.40	31.82	32.34	32.69	33.18	33.71	34.06	34.51
35	27.35	27.73	28.22	28.78	29.34	29.97	30.74	31.30	31.82	32.38
40	23.40	24.03	24.55	25.18	25.99	26.79	27.52	28.47	29.17	30.00
45	19.39	19.84	20.47	21.17	21.90	22.91	23.82	24.76	25.88	26.86
50	15.51	15.93	16.42	17.12	17.85	18.65	19.80	20.82	21.83	23.02
55	11.88	12.12	12.57	13.03	13.69	14.39	15.23	16.38	17.43	18.72
60	8.91	9.12	9.36	9.75	10.16	10.79	11.46	12.26	13.38	14.46
65	6.39	6.57	6.74	6.99	7.30	7.65	8.24	8.84	9.57	10.72
70	4.33	4.44	4.58	4.72	4.96	5.20	5.52	5.97	6.53	7.44
75	2.72	2.79	2.86	2.97	3.11	3.32	3.49	3.77	4.23	4.89
80	1.47	1.50	1.57	1.64	1.68	1.78	1.89	2.03	2.27	2.72

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

CANDELA TABULATION - (Cont.)

85	0.59	0.63	0.66	0.66	0.70	0.73	0.77	0.84	0.87	0.98
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Angles	**Horizontal Angles**									
	250	**255**	**260**	**265**	**270**	**275**	**280**	**285**	**290**	**295**
0	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18
5	38.14	38.21	38.25	38.35	38.42	38.53	38.49	38.49	38.56	38.49
10	38.18	38.25	38.32	38.39	38.49	38.63	38.74	38.77	38.77	38.70
15	37.83	37.93	38.04	38.07	38.18	38.28	38.49	38.63	38.74	38.67
20	37.30	37.41	37.44	37.51	37.72	38.00	38.07	38.00	38.18	38.28
25	36.19	36.43	36.68	37.09	37.34	37.34	37.30	37.51	37.58	37.55
30	34.82	35.21	35.49	35.80	36.08	36.22	36.33	36.47	36.54	36.43
35	32.97	33.36	33.74	34.20	34.44	34.65	34.79	34.82	34.82	34.72
40	30.60	31.19	31.68	31.99	32.38	32.55	32.73	32.80	32.66	32.38
45	27.63	28.26	28.82	29.20	29.51	29.79	29.97	29.97	29.69	29.31
50	24.10	24.83	25.43	25.92	26.27	26.44	26.62	26.51	26.13	25.39
55	19.73	20.78	21.48	22.01	22.53	22.67	22.67	22.18	21.55	20.71
60	15.75	16.84	17.85	18.41	18.83	19.04	18.83	18.16	17.19	16.14
65	12.02	12.96	13.76	14.43	14.74	14.88	14.53	13.83	12.99	11.74
70	8.31	9.29	9.99	10.48	10.90	11.00	10.62	9.68	8.80	8.00
75	5.52	6.29	7.09	7.51	7.72	7.82	7.54	6.74	5.66	5.00
80	3.35	3.95	4.68	5.31	5.59	5.69	4.86	3.84	3.32	2.83
85	1.08	1.22	1.33	1.40	1.43	1.47	1.43	1.33	1.22	1.12
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Angles	**Horizontal Angles**									
	300	**305**	**310**	**315**	**320**	**325**	**330**	**335**	**340**	**345**
0	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18	38.18
5	38.49	38.56	38.63	38.60	38.60	38.56	38.56	38.56	38.53	38.49
10	38.67	38.60	38.60	38.60	38.70	38.67	38.63	38.60	38.56	38.60
15	38.60	38.60	38.56	38.60	38.67	38.70	38.60	38.53	38.39	38.25
20	38.18	38.14	38.07	38.07	38.04	37.93	37.86	37.69	37.44	37.41
25	37.51	37.37	37.30	37.09	36.85	36.64	36.61	36.40	36.22	36.05
30	36.22	35.94	35.77	35.49	35.31	35.03	34.51	34.23	34.06	33.74
35	34.51	34.06	33.74	33.50	32.90	32.27	31.65	31.16	30.46	29.90
40	31.96	31.54	31.02	30.35	29.51	28.57	27.73	26.96	26.27	25.71
45	28.68	28.08	27.28	26.20	25.18	24.07	23.23	22.35	21.73	21.27
50	24.66	23.54	22.53	21.45	20.33	19.28	18.48	17.81	17.19	16.77
55	19.56	18.51	17.25	16.31	15.47	14.53	13.83	13.34	12.92	12.47
60	15.02	13.83	12.92	12.02	11.39	10.69	10.23	9.82	9.50	9.29
65	10.76	9.75	9.12	8.59	8.00	7.58	7.30	7.06	6.85	6.67
70	7.13	6.57	6.08	5.76	5.48	5.17	5.00	4.86	4.75	4.65
75	4.47	4.16	3.91	3.67	3.49	3.35	3.25	3.18	3.11	3.07
80	2.52	2.31	2.17	2.06	1.99	1.92	1.89	1.82	1.82	1.78
85	1.08	1.01	0.98	0.94	0.94	0.91	0.91	0.91	0.87	0.87
90	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00

Vert. Angles	**Horizontal Angles**		
	350	**355**	**360**
0	38.18	38.18	38.18
5	38.49	38.46	38.53
10	38.53	38.39	38.32
15	38.14	37.93	37.69

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES ROAD REPORT
PHOTOMETRIC FILENAME : L032110102.IES


CANDELA TABULATION - (Cont.)

20	37.30	37.16	36.99
25	35.87	35.70	35.52
30	33.43	33.18	32.87
35	29.48	29.24	29.13
40	25.43	25.08	24.80
45	20.75	20.43	20.26
50	16.42	16.10	16.00
55	12.19	12.05	11.95
60	9.08	8.94	8.91
65	6.57	6.50	6.50
70	4.58	4.54	4.54
75	3.04	3.00	3.00
80	1.75	1.75	1.75
85	0.87	0.87	0.87
90	0.00	0.00	0.00

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES ROAD REPORT
PHOTOMETRIC FILENAME : L032110102.IES

COEFFICIENTS OF UTILIZATION




FLUX DISTRIBUTION

	Lumens	Percent Of Luminaire
Downward Street Side	48.3	51.5
Downward House Side	45.5	48.5
Downward Total	93.8	100.0
Upward Street Side	0.0	0.0
Upward House Side	0.0	0.0
Upward Total	0.0	0.0
Total Flux	93.8	100.0

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES ROAD REPORT
PHOTOMETRIC FILENAME : L032110102.IES

POLAR GRAPH




Maximum Candela = 38.77 Located At Horizontal Angle = 290, Vertical Angle = 10
1 - Vertical Plane Through Horizontal Angles (290 - 110) (Through Max. Cd.)
2 - Horizontal Cone Through Vertical Angle (10) (Through Max. Cd.)

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES ROAD REPORT
PHOTOMETRIC FILENAME : L032110102.IES

ISOFOOTCANDLE LINES OF HORIZONTAL ILLUMINANCE




Distance In Units Of Mounting Height
Values Based On 3 Foot Mounting Height
1/2 Maximum Candela Trace Shown As Dashed Curve
(+) = Maximum Candela Point

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.

IES ROAD REPORT
PHOTOMETRIC FILENAME : L032110102.IES

LUMINAIRE CLASSIFICATION SYSTEM (LCS) GRAPH



Luminaire Lumens:
Front: Low=15.3, Medium=25.9, High=6.5, Very High=0.6
Back: Low=14.7, Medium=24.2, High=6.1, Very High=0.5
Uplight: Low=0.0, High=0.0

BUG Rating : B0-U0-G0

Photometric Toolbox® Copyright 2002-2019 by Lighting Analysts, Inc.
Calculations based on published IES Methods and recommendations, values rounded for display purposes.
Results derived from content of manufacturers photometric file.